

# Technical data sheet



## QD115300 DC battery charger



<b>Suitable HBC batteries:</b>	BA2130__, BA2140__, BT2130__, FuB 10 AA / XL
<b>Battery technology:</b>	NiMH
<b>Input voltage range:</b>	10 – 30 V DC
<b>Power consumption (without inserted battery):</b>	≤ 0.2 W
<b>Power consumption (with inserted battery):</b>	≤ 15 W
<b>Charge current:</b>	833.3 mA ±1%
<b>Charging time:</b>	BA2130__, BT2130__: ≤ 4h BA2140__: ≤ 3h
<b>Charging technique:</b>	Constant current (CC)
<b>Shutdown trigger:</b>	Peak Voltage Detection
<b>Status LEDs:</b>	Green: Illuminates when battery is charged. Orange: Illuminates when battery is charging. Red: Illuminates when battery is deep discharged or defective.
<b>Housing material:</b>	ABS plastic
<b>Dimensions:</b>	186 x 140 x 45 mm
<b>Weight:</b>	480 g
<b>Protection class:</b>	IP 40
<b>Temperature range:</b>	Operation: 0 – 45 °C Storage: -20 – 70 °C
<b>Applied standards:</b>	EN 61000-6-2 EN 61000-6-3